



## Intelligent Smoke Alarm

### Smoke and temperature monitoring for optimal fire detection

With the Intelligent Smoke Alarm from Develco Products, your customers will never have to worry about fire or smoke in their homes again, making the Intelligent Smoke Alarm essential for security, or home care solutions.

While at home, the Intelligent Smoke Alarm will warn your customer about smoke, using a loud sound. By connecting several Intelligent Smoke Alarms distributed in different places of the home, customers can hear the alarm of a fire in the basement while they are on the top floor.

While away, your customer will be instantly notified through an internet-connected gateway. No matter whether the user is at work, visiting friends and family or on holiday, the Intelligent Smoke Alarm keeps them informed regardless of their location.

Key features are:

- Smoke sensor - IAS Zone
- Temperature sensor
- European certification
- Zigbee certified

The Intelligent Smoke Alarm can also notify the user when the battery gets low ensuring the smoke alarm is not running out of power and preventing the alarm from going off at night due to low battery status. Through your IoT system, an Intelligent Smoke Alarm can be connected to other intelligent devices. For instance, smart lighting can be set to flash in cases of smoke detection.

Moreover, the Intelligent Smoke Alarm will report the status and temperature every two minutes via the customer's smart home system. The wireless smoke alarm is battery powered and easily mounted to the ceiling with the included screws.



- **Easy installation**
- **3 years+ battery lifetime**
- **Diameter 65 mm**



## Intelligent Smoke Alarm - Technical specifications

Model number: SMSZB-120

### General

Dimensions (Ø x H)	Ø 65 x 40 mm
Weight	80,3 g (with packaging: 111,7 g)
Color	White
Power supply	Battery: 1 x CR123, exchangeable Battery life: 3 years, reporting every 5 minutes Battery level and low battery warning can be reported
Radio	Sensitivity: -92 dBm Output power: Typ. +4 dBm
Environment	IP class: IP20 Operation temperature 0 to +50°C Relative humidity 10-95% non-condensing

### Functions

Smoke sensor	Optical Siren output 85 dB/3m
Temperature sensor	Range: 0 to +50°C Resolution: 0,1°C (accuracy Typ ±0,5°C and Max ±2°C) Sample time: config.: 2 s -65,000 s Reporting: configurable

### Communication

Wireless protocol	Zigbee Home Automation Zigbee end-device
-------------------	---

### Certifications

Conforming to CE, RED and RoHS directives  
DIN EN 14604 and DIN 14676 certified  
Zigbee Home Automation 1.2 certified